Document No. FR.GREY.DOP.v1.0

DECLARATION OF PERFORMANCE in accordance with Annex III of the Regulation (EU) No.305/2011

Revision Date: 01/11/18

**Python FR Grey** 



### 1. Unique identification code of the product type:

Python FR Grey

2. Batch / serial No. identifying the construction product as required under Article 11(4) NB.

Batch number is printed on the side of the pack with date of manufacture.

3. Intended use in accordance with the harmonised standard

Improved fast setting cement based adhesive with reduced slip.

4. Name & contact address of the Manufacturer

Python Adhesives Ltd

Teardrop Centre, London Road, Swanley, London, BR8 8TS

5. Name & contact address of the authorised representative whose mandate covers tasks specified in Article 12(2)

Not applicable

6. System of assessment & verification of constancy of performance as set out in Annex V

System 3+4

#### 7. Harmonised EN Standard

The notified body Ceram, identification No.1289, has carried out the initial type testing to System 3 and issued Test Report No.(135672)-23821

## 8. Declared Performance: To harmonised technical specification: EN 12004:2007 + A1:2012

Essential characteristics	Performance
Reaction to fire	Class F
Slip	0.06 mm
Early tensile adhesion strength	0.6 N/mm²
Initial tensile adhesion strength	1.5 N/mm²
Tensile adhesion strength after water immersion	1.0 N/mm²
Tensile adhesion strength after heat ageing	1.3 N/mm²
Tensile adhesion strength after freeze/thaw cycle	1.1 N/mm²
Tensile strength after 10 min open time	0.7 N/mm²
Dangerous substances	See MSDS

# **CLASSIFICATION C2 FT**

## 9. Declaration

The performance of the above product identified in points 1 & 2 is in conformity with the declared performance as defined under EN 12004:2007 + A1:2012. This declaration of performance is issued under the sole responsibility of The manufacturer identified in point 4.

Signed for on behalf of Python Adhesives Ltd by:

Ray Kingston

**Technical Support Representative**